

Asphalt Product

Vacuum Gas Oil (Summer) - LXR10

Product Code

101251

ISO 9001:2015

CGSB
94733



Copy

Description

A vacuum gas oil used for speciality asphalt product manufacture.

Property	ASTM NO.	Specification		Typical Analyses
		Min.	Max	
Density @ 15°C, kg/L	D 4052	0.9200	0.9500	0.9345
Distillation, °C	D 2887			
I.B.P.		190	-	217
5%		-	-	269
10%		-	-	287
50%		-	390	367
90%		-	-	452
95%		-	-	473
E.P.		-	550	525
Kinematic Viscosity @ 21°C, mm ² /s	D 7042	-	-	114
Kinematic Viscosity @ 40°C, mm ² /s	D 7042	16	45	36.5
Kinematic Viscosity @ 60°C, mm ² /s	D 7042	8	20	15.2
Flash Point (PMCC), °C	D 93	140	-	148
Aniline Point, °C	D 611	-	-	63
Pour Point, °C	D 97	-	6	<-14
Sulfur, %	D 4294	-	-	2.37
MCRT on 10 % Distillation Residue, %	D 4530	-	-	0.02
Ash Content	D 482	-	-	<0.01
H ₂ S, ppm	D 5504	-	-	4
BS&W, %	D1796/D96/D4007	-	-	<0.15

NOTE : Product Renamed with New Product Code (Previously Cutter Stock "C", Product Code 406)

Metals (D5185) and BTEX (GC), Bromine number (D1159) available upon request.