

Asphalt Product

# Vacuum Gas Oil (Winter) - LXR11

Product Code

## 101252

ISO 9001:2015

CGSB

94733



# Copy

### Description

A vacuum gas oil used for speciality asphalt product manufacture.

Property	ASTM NO.	Specification		Typical Analyses
		Min.	Max	
Density @ 15°C, kg/L	D 4052	0.9200	0.9400	0.9209
Distillation, °C	D 86			
I.B.P.	-	265	-	270
5%	-	-	-	293
10%	-	-	-	306
50%	-	-	-	370
90%	-	-	-	400+
95%	-	-	-	400+
E.P.	-	-	-	400+
Recovery, %	-	-	-	98.5
Residue, %	-	-	-	1
Loss,%	-	-	-	0.5
Kinematic Viscosity @ 21°C, mm <sup>2</sup> /s	D 7042	-	-	84.5
Kinematic Viscosity @ 40°C, mm <sup>2</sup> /s	D 7042	16	45	29.1
Kinematic Viscosity @ 60°C, mm <sup>2</sup> /s	D 7042	8	20	12.8
Flash Point (PMCC), °C	D 93	93	-	148
Aniline Point, °C	D 611	-	-	60
Pour Point, °C	D 97	-	-3	<-14
Sulfur, %	D 4294	-	2.5	2.37
MCRT	D 4530	-	0.04	0.02

NOTE : Product Renamed with New Product Code (Previously Cutter Stock "C" Winter Grade, Product Code 403)